



GLADIO V

FIELD-TESTED, FROM 2400 YEARS.

From the last legionary to the most important centurion, all of them had a Gladio.

Our roots are based in the history of a state that became an empire. The Victrix Gladio is our tribute to the main weapon of ancient Rome.

 **VICTRIX**
A R M A M E N T S

Destination use

Law Enforcement
Military
Sporting

Caliber

.308 Win. (1/11)
.260 Remington (1/8.5)
6,5 Creedmoor (1/8.5)

Barrel length

22"
26"

Weight

6.25 kg (13.78 lb) with empty magazine, muzzle brake, barrel length 22" and no scope
6.55 kg (14.44 lb) with empty magazine, muzzle brake, barrel length 26" and no scope

Dimension

Overall length closed: 868 mm (34.17")
Overall length open: 1113 mm (43.82")
With muzzle brake and barrel length 22"

Overall length closed: 969 mm (38.15")
Overall length open: 1215 mm (47.84")
With muzzle brake and barrel length 26"

Base rifle

Benchmark lapped barrel in AISI 416R match grade
Buttstock with horizontal and vertical multiple lever adjustments, retractable monopod with quick positioning adjustment and fine adjustment, and insulated cheek piece
Single feed and single stack 7-round magazine
Reversible EVO button folding system
Forend octagonal elliptic with M-LOK® system, integrated monobloc top rail 20 MoA and integrated monobloc rail for mounting a bipod STANAG 4694/Mil std 1913
Ergonomic and interchangeable grip
Action rail 20 MoA STANAG 4694/Mil std 1913
Detachable multifunction carry handle with quick mount:

- with QM (Quick mount) attachment for picatinny rail
- ergonomic handle
- integrated picatinny rail
- hook for rope attachment
- QD (Quick detach) attachments
- tripod attachment with 1/4" – 20 UNC and 3/8" – 16 UNC threads
- front magnetic bit holder for field maintenance

 Victrix ProAngle detachable muzzle brake featuring 3 forward-canted chambers
Short action in AISI 630 worked out from billet through milling and turning with finish on electro-discharge and grinding machinery.
Bolt with three asymmetric lugs: first lug on top of the cylinder in vertical position (at 12 o'clock), two side lugs arranged at an angle of 105 degree lift, dirt/ice grooves integral
Matt PVD finish on the action and polished PVD finish on the bolt
Victrix Professional Dual-stage trigger, convertible to a single stage trigger, with two positions top safety
Bag for a safe transport in rifle case
Explorer case for transport with military specifications cod. 13513
User manual and welcome kit

Stock colour

Every and each component made of light alloy undergoes a 30 micron hard black anodising
CERAKOTE ceramic polymer firearm coatings available in three colours:

Dark Grey
Dark Olive Drab Green
Medium Flat Brown

Optional

Side rails for forend with M-LOK® system STANAG 4694/Mil std 1913



VICTRIX
PROFESSIONAL